




PosterBOX Slim 2

Side illumination for shallow light boxes

PosterBOX™ Slim 2 washes light across single-sided and double-sided displays using FanFlare™ lens technology that optimises the light inside the box. The result is uniform light without the stripes associated with fluorescent tubes. The narrow silhouette of the side mounted modules makes PosterBOX Slim 2 an excellent option for single-sided sign boxes as shallow as 50 mm and double-sided cabinets as shallow as 100 mm.



- PosterBOX Slim 2 is 40% brighter than PosterBOX Slim
- Excellent white light intensity and uniformity
- Optimal for applications as shallow as 50 mm:
 - Indoor textile prints
 - Movie posters
 - Cabinets using FlexFace®

Specifications

| | | |
|------------------------------|--|---------------|
| Part number | White (6500 K) | 701946-6WXLP2 |
| | White (5000 K) | 701946-5WXLP2 |
| Dimensions L × W × H | 124 mm × 26 mm × 16 mm | |
| Viewing angle | 15° × 43° | |
| LEDs per module | 3 | |
| Modules per meter* | 6,5 | |
| Minimum box depth | Single-sided | 50 mm |
| | Double-sided | 100 mm |
| Operating temperature | -40° C to +70° C | |
| Protection class | IP66 | |
| Special features | FanFlare lens technology | |
| Power per module | 1,8 W | |
| Efficacy | 94 lm/W | |
| Power capacity | 30 modules per SloanLED 60 W 12 VDC power supply | |
| Fastening | Peel-n-stick and mechanical | |
| Packaging | 38 modules per tray, 3 trays per carton | |
| Colour temperatures | 6500 K, 5000 K | |
| Lumens per module | 170 | |

*Based on recommended module spacing.

Green Signage 

